

Safety & Security Doors

Your new Aluminium Safety/Security Door has been manufactured using the highest quality materials available to the industry. With a moderate amount of maintenance, your Aluminium Safety/Security Door will retain its good looks, and resist the elements for years to come. Depending on how harsh the environmental elements are, the maintenance period will vary.

Your Aluminium Safety/Security Door should only ever need to be washed down with a soft bristled brush using warm water and a mild detergent. Rinse well with fresh water to remove any detergent residue. Care should be taken to avoid excessive amounts of water entering the main lock. Strong detergents and abrasive cleaners should never be used to clean your Aluminium Safety/Security Door as these may scratch or damage the surface finish.

Periodic lubrication of the main lock (and any other auxillary lock components) should only ever be done using a graphite powder or silicon spray. Liquid or aerosol lubricants (such as WD40) can cause corrosion and damage the locking mechanism and should never be used as this **will void any warranties on the product**.

SUGGESTED MAINTENANCE PERIOD TABLE

MILD (being rural, away from the coast and remote from industry and urban activity)	6 Months
MODERATE (being mainly urban, inland and away from heavy industry)	3 Months
TROPICAL/SEVERE (being coastal/marine, subject to salt deposition and within 15km of the Eastern Coast, or 10km of the Western Coast of Australia)	2-4 Weeks